




INA BRAINGS SALES JAPAN CO.,LTD.



10 mm x 22 mm x 6 mm FAG HSS71900-E-T-P4S angular contact ball bearings

Bearing No. HSS71900-E-T-P4S

HSS71900-E-T-P4S Bearing 2D drawings and 3D CAD models

Size	10x22x6 mm
Bore Diameter	10 mm
Outer Diameter	22 mm
Width	6 mm
d	10 mm
D	22 mm
B	6 mm
a	7 mm
D_a	19,5 mm / Tolerance: H12
d_a	13 mm / Tolerance: h12
$r_{a \max}$	0,3 mm
r_{\min}	0,3 mm
	25 ° / Angle
m	0,012 kg / Weight
C_r	1700 N / Dynamic load rating (radial)
C_{0r}	620 N / Static load rating (radial)
$n_{G \text{ Fett}}$	95000 1/min / Limiting speed for grease lubrication
Size	10x22x6 mm
Bore Diameter	10 mm
Outer Diameter	22 mm
Width	6 mm
d	10 mm
D	22 mm



INA BRAINGS SALES JAPAN CO.,LTD.

B	6 mm
C	6 mm
Angle ()	25 °
a	7 mm
r min.	0,3 mm
Da	19,5 mm
ra max.	0,3 mm
da	13 mm
Weight	0,01 Kg
Basic dynamic load rating (C)	1 860 kN
Basic static load rating (C0)	1 040 kN
(Grease) Lubrication Speed	75 000 r/min